



SECTION I: PRODUCT INFORMATION

PRODUCT: SIKAFLEX® 1A REVISION DATE: February 15, 2005

USAGE: ONE COMPONENT URETHANE BASED SEALANT

MANUFACTURER: SIKA CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: Not Regulated WHMIS Classification: D2A, B3
UN NUMBER: Not Established Class: Not Applicable
Packaging Group: Not Applicable

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (species, route)	LC ₅₀ (species, route)
CALCIUM OXIDE	1-5	Not Available	1305-78-8	Not Available	Not Available
XYLENE	5-10	100 ppm	1330-20-7	4300 (oral, rat)	6350 ppm/4h
POLYOL AND ISOCYANATE PREPOLYMER	15-40	Not Established	Not Available	Not Established	Not Established

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Paste
Appearance and Odor: Aromatic odor grey paste
Odor Threshold: Not Established
Evaporation Rate: Not Established
Vapor Density: Not Established
Vapor Pressure: Not Established

Boiling Point: Not Established
Freezing Point: Not Established
Density: 1,2 g/ml
Water Solubility: Not Established
PH: Not Established
% volatile: < 4%
Water/Oil Distribution: Not Established



PRODUCT: SIKAFLEX® 1A

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: If Yes, under what conditions:	Combustible Flame, spark	TDG inflammability Class: Flammable upper limits (% vol.): Flammable lower limits (% vol.): Flash Point (method used): Auto-ignition temperature:	Not Regulated Not Established Not Established > 80°C (TCC) Not Established
Extinguishing methods:	Foam, dry chemical products, CO ₂ , water for large flames.	Dangerous Combustion Products:	Carbon oxides, Aldehydes Ketones, HCL, Nitrogen oxide, MDI, TDI
Special Methods:	Firefighters must wear complete protective clothing with respiratory equipment and they must protect any exposed skin. Heated isocyanates react strongly with water.	Protect from mechanical impact: Protect from static discharge:	No No

SECTION V: REACTIVITY DATA

Chemical stability: If not, under what conditions	Yes	Dangerous decomposition products:	Carbon oxides, Aldehydes Ketones, HCL, Nitrogen oxide, MDI, TDI
Incompatibility with other material: If Yes, which ones:	Yes Acid, strong oxidizer, amine.	Polymerization Risks:	No



PRODUCT: SIKAFLEX® 1A

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: Irritating

Skin: Irritating
Contact may result in dermatitis, allergic reactions, and sensitization.

Inhalation: Vapor or mist from this product may cause irritation.

Ingestion: May cause nausea, vomiting, diarrhea, gastro-intestinal system disorder, constipation.

Carcinogenicity: No

Toxic effects on reproduction: No

Teratogenicity: Xylene is classified as a development toxicant (Embryo toxin)

Mutagenicity: No

Product with synergistic effects: Not Established

Over exposure may cause breathing difficulties, sensitization, headaches, nausea, vomiting. May aggravate respiratory, skin, eye, lung problems and allergies.

If the product is applied according to the manufacturer, none of these symptoms should be encountered.

A person who is sensitized to isocyanate may have a reaction with a level of isocyanate well below the T.L.V.

Xylene is a central nervous system depressor and in rare cases, may cause a sensitization of the heart muscle causing arrhythmia.

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems. An over exposure may cause death.



PRODUCT: SIKAFLEX® 1A

SECTION VII: PREVENTIVE MEASURES

INDIVIDUAL EQUIPMENT PROTECTION

Gloves: Use chemical resistant gloves.

Respiratory equipment: Not necessary under normal use.

Eyes: Full-face mask or safety glasses

Shoes: Ordinary

Clothing: Rubber Apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required.

Procedure in case of leaks: Absorb with sand or other absorbent material.

Handling and Equipment methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry and well ventilated area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: SIKAFLEX® 1A

SECTION VIII: FIRST AID

Skin: Remove contaminated clothing and shoes.
Wash immediately with plenty of water.
Wash clothing before re-wearing.
Consult a physician if required.

Eyes: Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash.
See a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.
Do not give anything by mouth to an unconscious person.
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared by: Steve Gosselin
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.